

**PAT-NO:** JP02000193478A  
**DOCUMENT-IDENTIFIER:** JP 2000193478 A  
**TITLE:** NAVIGATION SYSTEM  
**PUBN-DATE:** July 14, 2000

**INVENTOR-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
OZAWA, KENICHI	N/A

**ASSIGNEE-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
CLARION CO LTD	N/A

**APPL-NO:** JP10376542  
**APPL-DATE:** December 24, 1998

**INT-CL (IPC):** G01C021/00 , G08G001/0969

**ABSTRACT:**

**PROBLEM TO BE SOLVED:** To guide following the driver's intention by setting a new route with a not-yet-passed point as a passed point based on the distance from the not-yet- passed point to a car position if a car is judged to leave apart from the not-yet-passed point.

**SOLUTION:** When a requested specific transit point along with a destination are inputted from an input part 19, a route calculating part 22 calculates a route to the destination and displays it on a display part 28. A route guide control part 26 measures, while guiding car

with a screen display, etc., a distance from a current position from a specific point, and if a current measured value is larger than the distance previously measured and stored, a current position is judged to be out of the set route for starting a timer measurement, with the route calculating part 22 setting a new route. When a timer value is 5 minute or more with timer measurement already started, a car is judged to be away from the next specific point in one direction, and a driver is judged to have intentionally canceled the next specific-point transit, a cancel is confirmed with a sound-value output part, etc., and a route to a destination is set while the specific point is assumed as has been passed.

COPYRIGHT: (C)2000,JPO